



GMI LM2LL Overlaminate
2.0 Mil Luster Cast Vinyl
With UV Protection

The semi-gloss finish of the cast vinyl film reduces glare and still provides an excellent view of the underlying printed image. The overlaminate adhesive wets out quickly to provide a clean image. The stabilized vinyl film offers excellent protection from UV radiation to enhance the weathering of the underlying graphics.

CONSTRUCTION

Applications	Used for overlaminating printed vinyl films.
Face Film	2.0 Mil
Adhesive Release	20 min. 32 oz./in. 24 hrs. 50 oz/in.
Liner	50 # Kraft with UV Protection

PHYSICAL PROPERTIES

Outdoor Durability	5 years.
Minimum Surface/Ambient Air Application Temperature	+ 50° F.
Adhesive	Permanent acrylic
Application Surface	+ 50° F.
Service Temperature Range	- 50° F. to 225° F.
Opacity	Clear
Product Thickness	2.0 Mil
Chemical Resistance	Distilled water (24 hrs.) no effect; Detergent (24 hrs.) no effect; Gasoline (10 minutes) no effect.
Water Resistance	Excellent.
Finish	Semi-Gloss.
Shelf Life	@ 73, 50 % RH

Sizes	LM2LL3025	30" X 25 YDS
	LM2LL3050	30" X 50 YDS
	LM2LL3610	36" X 10 YDS
	LM2LL3625	36" X 25 YDS
	LM2LL3650	36" X 50 YDS
	LM2LL4810	48" X 10 YDS
	LM2LL4825	48" X 25 YDS
	LM2LL4850	48" X 50 YDS
	LM2LL5425	54" X 25 YDS
	LM2LL5450	54" X 50 YDS
	LM2LL6025	60" X 25 YDS
	LM2LL6050	60" X 50 YDS

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.

©2008 Graphic Materials International.
All rights reserved. LM2LL 082808.